



								未注线性尺寸极限偏差 Unmarked tolerance	
								0.5-3	±0.2
减速比 (Ratio i)	i推荐	12/16/20/28	15/25/35/40		70			3-6	±0.3
	i不推荐		30/45/50	60		64/80	90	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	345	335	300	290	265	255	30-120	±0.8
最大加速力矩(Max.acceleration torque)	Nm	621	603	540	522	477	459	120-400	±1.2
急停扭矩(Emergency stop toque)	Nm	1035	1005	900	870	795	765	400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)	6700N	空载力矩20℃(No-load torque)			≤ 0.36Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	3300N	润滑(Lubrication)			合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)			-15℃~+90℃			组氏连特	
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)			≥20000h			AB115L2-i-P2-S2	
噪音 (Noise)	≤ 63db	防护等级(Protection grade)			IP54			22-58-110-145-M8	
回程间隙 (Backlash)	7arcmin	AB系列		Tel/电话: 0533-6288333 6288444			A. AB. 115.		
		P2 L2		Fax/传真: 0533-6288411					
				Web/网址: www.newstart.cn					