


减速比 (Ratio i)	i	3	4	5	6	7	8	9	10	30	±0.5
额定承载扭矩(Rated load torque)	Nm	450	700	650	610	540	510	455	455	60-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	810	1260	1170	1098	972	918	819	819	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	1350	2100	1950	1830	1620	1530	1365	1365	400-1000	±2
精密行星减速机技术参数										精密行星减速机	
容许最大径向载荷 (Max.radial load)		9600N	空载力矩20℃(No-load torque)				≤ 0.36Nm				 NEWSTART 纽氏達特
容许最大轴向载荷 (Max.axial load)		4800N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃				
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)				≥20000h				
噪音 (Noise)		≤ 65db	防护等级 (Protection grade)				IP54				
回程间隙 (Backlash)		5arcmin	AB系列			Tel/电话: 0533-6288333 6288444				A. AB. 142.	
			P2 L1			Fax/传真: 0533-6288411					
						Web/网址: www.newstart.cn					