


减速比 (Ratio i)	i 推荐	12/16/20/32	15/25/35/40				0.5-3	±0.2
	i 不推荐		30/45/50	60	64/80	90	3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	23	21	20	18	14	6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	41.4	37.8	36	32.4	25.2	30-120	±0.8
急停扭矩 (Emergency stop torque)	Nm	69	63	60	54	42	120-400	±1.2
							400-1000	±2
精密行星减速机技术参数							精密行星减速机	
容许最大径向载荷 (Max. radial load)	770N	空载力矩20℃ (No-load torque)			≤ 0.05Nm			AB042L2-i-P2-S2 8-25-30-46-M4
容许最大轴向载荷 (Max. axial load)	380N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃			
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h			
噪音 (Noise)	≤ 58db	防护等级 (Protection grade)			IP54		A. AB.	042.
回程间隙 (Backlash)	7arcmin			AB系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			
				P2 L2				