


減速比 (Ratio i)		4	5	7	8	10
額定承載扭矩(Rated load torque)	Nm	1483	1200	1000	1000	910
最大加速力矩(Max.acceleration torque)	Nm	2669	2160	1800	1800	1638
急停扭矩 (Emergency stop toque)	Nm	4449	3600	3000	3000	2730

未注线性尺寸极限偏差 Unmarked tolerance
----------------------------------

0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机技术参数			
容许最大径向载荷 (Max. radial load)	26600N	空载力矩20℃ (No-load torque)	≤ 1.5Nm
容许最大轴向载荷 (Max. axial load)	18000N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 70db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	13arcmin	ADR系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411
		P2 L1	Web/网址: www.newstar.cn

	精密行星减速机 Precision Planetary Gear Boxes
	 <b>NEWSTART</b> 紐氏達特
	ADR200L1-i-P2-0P2 42-113-114.3-200-M12
	A. ADR. 200.