



减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200	未注线性尺寸极限偏差 Unmarked tolerance	
	i 不推荐	256/320	512	
额定承载扭矩 (Rated load torque)	Nm	345	265	0.5-3 ±0.2
最大加速力矩 (Max.acceleration torque)	Nm	621	477	3-6 ±0.3
急停扭矩 (Emergency stop torque)	Nm	1035	795	6-30 ±0.5
*备注三级减速机需与厂家沟通				30-120 ±0.8
				120-400 ±1.2
				400-1000 ±2

精密行星减速机技术参数			精密行星减速机
容许最大径向载荷 (Max.radial load)	2900N	空载力矩20℃ (No-load torque)	≤ 0.2Nm
容许最大轴向载荷 (Max.axial load)	1950N	润滑 (Lubrication)	合成润滑脂
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 68db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	15arcmin	AER系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn
			A. AER. 120.