


减速比 (Ratio i)	i	3	4	5	6	7	8	9	10	6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	220	345	335	300	290	265	255	255	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	396	621	603	540	522	477	459	459	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	660	1035	1005	900	870	795	765	765	400-1000	±2

精密行星减速机技术参数										精密行星减速机	
容许最大径向载荷 (Max.radial load)	2900N	空载力矩 (No-load torque)					≤ 0.36Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	1950N	润滑油 (Lubrication)					合成润滑脂			 纽氏達特	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)					-15℃~+90℃			AE120L1-i-P2-S2 24-58-110-145-M8	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)					≥20000h				
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)					IP54				
回程间隙 (Backlash)	5arcmin	AE系列					Tel/电话: 0533-6288333 6288444			A. AE. 120.	
		P2 L1					Fax/传真: 0533-6288411				
							Web/网址: www.newstart.cn				