


								未注线性尺寸极限偏差 Unmarked tolerance	
								0.5-3	±0.2
								3-6	±0.3
减速比 (Ratio i)	i推荐	12/16/20/32	15/25/35/40		70			6-30	±0.5
	i不推荐		30/45/50	60		64/80	90	30-120	±0.8
额定承载扭矩(Rated load torque)	Nm	345	335	300	290	265	255	120-400	±1.2
最大加速力矩 (Max.acceleration torque)	Nm	621	603	540	522	477	459	400-1000	±2
急停扭矩 (Emergency stop toque)	Nm	1035	1005	900	870	795	765		
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	2900N	空载力矩(No-load torque)			≤ 0.2Nm			 ® 纽氏達特	
容许最大轴向载荷 (Max.axial load)	1950N	润滑(Lubrication)			合成润滑油				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)			-15℃~+90℃				
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h			AE120L2-i-P2-S2 19-40-70-90-M5	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)			IP54			A. AE. 120.	
回程间隙 (Backlash)	7arcmin			AE系列		Tel/电话: 0533-6288333 6288444			
				P2 L2		Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			