

1

2

3

4

5



6

A

B

C

D



A

B


C

D

减速比 (Ratio i)	i	3	4	5	6	7	8	9	10
额定承载扭矩 (Rated load torque)	Nm	55	65	60	52	50	45	42	42
最大加速力矩 (Max. acceleration torque)	Nm	99	117	108	93.6	90	81	75.6	75.6
急停扭矩 (Emergency stop torque)	Nm	165	195	180	156	150	135	126	126

未注线性尺寸极限偏差	
0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机技术参数			
容许最大径向载荷 (Max. radial load)	950N	空载力矩20℃ (No-load torque)	$\leq 0.1Nm$
容许最大轴向载荷 (Max. axial load)	740N	润滑 (Lubrication)	合成润滑油
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000h$
噪音 (Noise)	$\leq 63db$	防护等级 (Protection grade)	IP54
回程间隙 (Return clearance)	9arcmin	AER系列	Tel/电话: 0533-6288333 6288444
		P2 L1	Fax/传真: 0533-6288411
			Web/网址: www.newstart.cn

精密行星减速机	
Precision Planetary Gear Boxes	
	
AER070L1-i-P2-S2	
8-24-38.1-1147.14-M4	
A. AER.	070.

1

2

3

4

5

6