

1

2

3

4

5

6

A

B

C


D

A

B

C

D



减速比 (Ratio i)	i	3	4	5	6	7	8	9	10
额定承载扭矩 (Rated load torque)	Nm	55	65	60	52	50	45	42	42
最大加速力矩 (Max. acceleration torque)	Nm	99	117	108	93.6	90	81	75.6	75.6
急停扭矩 (Emergency stop torque)	Nm	165	195	180	156	150	135	126	126

未注线性尺寸极限偏差	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)	950N	空载力矩20℃ (No-load torque)		≤ 0.1Nm		
容许最大轴向载荷 (Max. axial load)	740N	润滑 (Lubrication)		合成润滑脂		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	9arcmin		AER系列	Tel/电话: 0533-6288333 6288444		
			P2 L1	Fax/传真: 0533-6288411		
				Web/网址: www.newstart.cn		
				A. AER. 070.		

1

2

3

4

5

6