



减速比 (Ratio i)	i 推荐	12/16/20/32	15/25/35/40		70		
	i 不推荐		30/45/50	60		64/80	90
额定承载扭矩 (Rated load torque)	Nm	65	60	52	50	45	42
最大加速力矩 (Max. acceleration torque)	Nm	117	108	93.6	90	81	75.6
急停扭矩 (Emergency stop torque)	Nm	195	180	156	150	135	126

精密行星减速机技术参数					
容许最大径向载荷 (Max. radial load)	950N	空载力矩20℃ (No-load torque)		≤ 0.1Nm	
容许最大轴向载荷 (Max. axial load)	740N	润滑 (Lubrication)		合成润滑脂	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)		IP54	
回程间隙 (Backlash)	11arcmin	AER系列		Tel/电话: 0533-6288333 6288444	
Fax/传真: 0533-6288411					
Web/网址: www.newstart.cn					
		P2 L2			

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机 Precision Planetary Gear Boxes	
	
AER070L2-i-P2-S2 14-30-50-70-M4	
A. AER.	070.