



				未注线性尺寸极限偏差 Unmarked tolerance	
减速比 (Ratio i)	i 推荐	60/64/80/100/120/160/200			
	i 不推荐	256/320		512	0.5-3 ±0.2
额定承载扭矩 (Rated load torque)	Nm	65		45	3-6 ±0.3
最大加速力矩 (Max.acceleration torque)	Nm	117		81	6-30 ±0.5
急停扭矩 (Emergency stop torque)	Nm	195		135	30-120 ±0.8
					120-400 ±1.2
*备注三级减速机需与厂家沟通					400-1000 ±2
精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes
容许最大径向载荷 (Max.radial load)	950N	空载力矩 (No-load torque)		≤ 0.1Nm	 紐氏達特
容许最大轴向载荷 (Max.axial load)	740N	润滑 (Lubrication)		合成润滑脂	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h	AE070L3-i-P2-S2 8-25-30-46-M4
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)		IP54	
回程间隙 (Backlash)	9arcmin	AE系列		Tel/电话: 0533-6288333 6288444	A. AE. 070.
				Fax/传真: 0533-6288411	
				Web/网址: www.newstart.cn	