



减速比 (Ratio i)				未注线性尺寸极限偏差 Unmarked tolerance	
				0.5-3	±0.2
额定承载扭矩 (Rated load torque)				3-6	±0.3
最大加速力矩 (Max. acceleration torque)				6-30	±0.5
急停扭矩 (Emergency stop torque)				30-120	±0.8
				120-400	±1.2
*备注三级减速机需与厂家沟通				400-1000	±2
精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	1600N	空载力矩20℃ (No-load torque)	≤ 0.2Nm	 紐氏達特 AER090L3-i-P2-S2 19-40-80-100-M6	
容许最大轴向载荷 (Max. axial load)	1500N	润滑 (Lubrication)	合成润滑油		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)	IP54	A. AER. 090.	
回程间隙 (Backlash)	12arcmin	AER系列			
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	