


减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80	3-6	±0.3	
额定承载扭矩 (Rated load torque)		Nm	125	260	230	120	6-30	±0.5
最大加速力矩 (Max. acceleration torque)		Nm	225	468	414	216	30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	375	780	690	360	120-400	±1.2
							400-1000	±2
精密行星减速机技术参数							精密行星减速机	
容许最大径向载荷 (Max. radial load)		3600N	空载力矩20℃ (No-load torque)		≤ 0.72Nm		Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)		8000N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)			
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		PF142L2-i-P2-S2	
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)		≥20000h		35-79-114.3-200-M12	
噪音 (Noise)		≤ 65db	防护等级 (Protection grade)		IP54			
回程间隙 (Backlash)		12arcmin	PL系列		Tel/电话: 0533-6288333 6288444		A. PF. 142.	
			P2 L2		Fax/传真: 0533-6288411			
					Web/网址: www.newstart.cn			