


减速比 (Ratio i)	60/64/80/160/256		100/120/200/320	512	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	800	700	450	30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	1440	1260	810	120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	2400	2100	1350	400-1000	±2
精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max.radial load)	3600N	空载力矩20℃ (No-load torque)		≤ 0.72Nm	Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	8000N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)		
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃	WPF142L1.1-P2-S2	
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)		≥20000h	32-58-130-165-M8	
噪音 (Noise)	≤ 70db	防护等级 (Protection grade)		IP54	A. WPF. 142.	
回程间隙 (Backlash)	18arcmin	PL系列		Tel: 电话: 0632-6288233 6288444		
		P2 L3		Fax: 传真: 0632-6288411		
				Web: 网站: www.newstar.cn		

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3



	WPF142L3-i-P2-S2
	32-58-130-165-M8

A. WPF.	142.
---------	------