


减速比 (Ratio i)		60/64/80/160/256		100/120/200/320		512		6-30		±0.5			
额定承载扭矩 (Rated load torque)		Nm		800		700		450		30-120		±0.8	
最大加速力矩 (Max.acceleration torque)		Nm		1440		1260		810		120-400		±1.2	
急停扭矩 (Emergency stop torque)		Nm		2400		2100		1350		400-1000		±2	
精密行星减速机技术参数									精密行星减速机				
容许最大径向载荷 (Max.radial load)		3600N		空载力矩20℃ (No-load torque)				≤ 0.72Nm		Precision Planetary Gear Boxes			
容许最大轴向载荷 (Max.axial load)		8000N		润滑 (Lubrication)				合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)		2000r/min		使用环境温度 (Operation temperature)				-15℃~+90℃		NEWSTART 纽氏達特			
最大输入转速 (Max input speed)		4000r/min		使用寿命 (Service life)				≥20000h		WPF142L3-i-P2-S2			
噪音 (Noise)		≤ 70db		防护等级 (Protection grade)				IP54		35-79-114.3-200-M12			
回程间隙 (Backlash)		18arcmin		PL系列		Tel/电话: 0533-6288333 6288444		A. WPF. 142.					
				P2 L3		Fax/传真: 0533-6288411							
						Web/网址: www.newstart.cn							