



未注线性尺寸极限偏差 Unmarked tolerance				0.5-3	±0.2
				3-6	±0.3
				6-30	±0.5
				30-120	±0.8
				120-400	±1.2
				400-1000	±2
精密行星减速机技术参数					
减速比 (Ratio i)	60/64/80/160/256		100/120/200/320	512	
额定承载扭矩 (Rated load torque)	Nm	110	90	50	
最大加速力矩 (Max.acceleration torque)	Nm	198	162	90	
急停扭矩 (Emergency stop torque)	Nm	330	270	150	
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃ (No-load torque)	≤ 0.2Nm		
容许最大轴向载荷 (Max.axial load)	1200N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54		
回程间隙 (Backlash)	20arcmin	PL系列	Tel/电话: 0533-6288333 6288444		
		P2 L3	Fax/传真: 0533-6288411		
			Web/网址: www.newstart.cn		
				A. PF.	080.

精密行星减速机  
Precision Planetary  
Gear Boxes

PF080L3-i-P2-S2  
14-30-50-70-M5