


|                                      |     |             |                |       |
|--------------------------------------|-----|-------------|----------------|-------|
| 减速比 (Ratio i)                        | 9   | 12/16/20/32 | 15/40/25/50/30 | 64/80 |
| 额定承载扭矩 (Rated load torque) Nm        | 40  | 110         | 90             | 50    |
| 最大加速力矩 (Max. acceleration torque) Nm | 72  | 198         | 162            | 90    |
| 急停扭矩 (Emergency stop torque) Nm      | 120 | 330         | 270            | 150   |

|                                  |      |
|----------------------------------|------|
| 未注线性尺寸极限偏差<br>Unmarked tolerance |      |
| 0.5-3                            | ±0.2 |
| 3-6                              | ±0.3 |
| 6-30                             | ±0.5 |
| 30-120                           | ±0.8 |
| 120-400                          | ±1.2 |
| 400-1000                         | ±2   |

|                              |           |                                |   |  |
|------------------------------|-----------|--------------------------------|---|--|
| 精密行星减速机技术参数                  |           |                                |   | 精密行星减速机<br>Precision Planetary<br>Gear Boxes   |
| 容许最大径向载荷 (Max. radial load)  | 900N      | 空载力矩20℃ (No-load torque)       | ≤ 0.2Nm   | <br>PF080L2-i-P2-S2<br>22-58-110-145-M8 |
| 容许最大轴向载荷 (Max. axial load)   | 1200N     | 润滑 (Lubrication)               | 合成润滑油 (Synthetic grease)  |  |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | -15℃~+90℃   |  |
| 最大输入转速 (Max input speed)     | 6000r/min | 使用寿命 (Service life)            | ≥20000h   |  |
| 噪音 (Noise)                   | ≤ 60db    | 防护等级 (Protection grade)        | IP54  | A. PF. 080.  |
| 回程间隙 (Backlash)              | 12arcmin  | PL系列                           | Tel/电话: 0533-6288333 6288444<br>Fax/传真: 0533-6288411<br>Web/网址: www.newstart.cn |  |
|                              |           | P2 L2                          |   |  |