


减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5	
额定承载扭矩(Rated load torque)		Nm	110	90	50	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	198	162	90	120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm	330	270	150	400-1000	±2
精密行星减速机技术参数						精密行星减速机	
容许最大径向载荷 (Max.radial load)		900N	空载力矩20℃(No-load torque)		≤ 0.2Nm		Precision Planetary Gear Boxes
容许最大轴向载荷 (Max.axial load)		1200N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)		-15℃ +90℃		
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)		≥20000h		PF080L3-i-P2-S2
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)		IP54		19-40-80-100-M6
回程间隙 (Backlash)		20arcmin	PL系列		Tel/电话: 0533-6288333 6288444		A. PF. 080.
			P2 L3		Fax/传真: 0533-6288411		
					Web/网址: www.newstart.cn		