




未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	1850N	空载力矩20℃(No-load torque)	≤ 0.36Nm	 NEWSTART® 纽氏達特
容许最大轴向载荷 (Max. axial load)	2800N	润滑(Lubrication)	合成润滑脂 (Synthetic grease)	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)	-15℃~+90℃	
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)	≥20000h	
噪音 (Noise)	≤ 63db	防护等级(Protection grade)	IP54	
回程间隙 (Backlash)	14arcmin	PL系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	Precision Planetary Gear Boxes PL120L3-i-P2-S2 24-58-110-145-M8 A. PL. 120.
		P2 L3		

精密行星减速机
Precision Planetary
Gear Boxes



PL120L3-i-P2-S2
24-58-110-145-M8

Tel/电话: 0533-6288333 6288444
Fax/传真: 0533-6288411
Web/网址: www.newstart.cn

A. PL. 120.