



减速比 (Ratio i)		60/64/80/160/256		100/120/200/320		512		6-30		±0.5			
额定承载扭矩 (Rated load torque)		Nm		260		230		120		30-120		±0.8	
最大加速力矩 (Max.acceleration torque)		Nm		468		414		216		120-400		±1.2	
急停扭矩 (Emergency stop torque)		Nm		780		690		360		400-1000		±2	
精密行星减速机技术参数										精密行星减速机			
容许最大径向载荷 (Max.radial load)		900N		空载力矩20℃ (No-load torque)				≤ 0.36Nm		Precision Planetary Gear Boxes			
容许最大轴向载荷 (Max.axial load)		1200N		润滑 (Lubrication)				合成润滑脂 (Synthetic grease)		 紐氏達特			
额定输入转速 (Nominal input speed)		3000r/min		使用环境温度 (Operation temperature)				-15℃~+90℃		WPL120L3-i-P2-S2 24-58-110-145-M8			
最大输入转速 (Max input speed)		6000r/min		使用寿命 (Service life)				≥20000h					
噪音 (Noise)		≤ 68db		防护等级 (Protection grade)				IP54					
回程间隙 (Backlash)		18arcmin		WPL系列		Tel/电话: 0533-6288333 6288444		Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		A. WPL. 120.			
				P2 L3									