

1 2 3 4 5 6


A

B



C

D

输出端 Output



输入端 Input




A

B

C

D

减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80				6-30	±0.5
额定承载扭矩(Rated load torque)		Nm	400	800	700	450			30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	720	1440	1260	810			120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm	1200	2400	2100	1350			400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max.radial load)		3600N	空载力矩20℃ (No-load torque)			≤ 0.72Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		8000N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)			 纽氏达特	
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃			PL160L2-i-P2-S2 38-80-180-215-M12	
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)			≥20000h				
噪音 (Noise)		≤ 65db	防护等级 (Protection grade)			IP54				
回程间隙 (Backlash)		12arcmin	PL系列			Tel/电话: 0533-6288333 6288444			A. PL. 160.	
			P2 L2			Fax/传真: 0533-6288411				
						Web/网址: www.newstart.cn				

1 2 3 4 5 6