


減速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80			
額定承載扭矩 (Rated load torque)	Nm	22	45	41	18			
最大加速力矩 (Max. acceleration torque)	Nm	39.6	81	73.8	32.4			
急停扭矩 (Emergency stop torque)	Nm	66	135	123	54			

未注线性尺寸极限偏差 Unmarked tolerance	
----------------------------------	--

0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)	480N	空载力矩20℃(No-load torque)		≤ 0.1Nm		
容许最大轴向载荷 (Max. axial load)	600N	润滑(Lubrication)		合成润滑油 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)		≥20000h		
噪音 (Noise)	≤ 63db	防护等级(Protection grade)		IP54		
回程间隙 (Backlash)	16arcmin	WPL系列		Tel/ 电话: 0533-6288333 6288444		
		P2 L2		Fax/ 传真: 0533-6288411		
				Web/ 网址: www.newstart.cn		
				 <b>NEWSTART</b> 纽氏达特		
				WPL060L2-i-P2-S2		
				8-24-38. 1-147. 14-M4		
				A. WPL. 060.		