

1

2

3

4

5



6

A

B

C

D



A

B

C

D

减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512
额定承载扭矩 (Rated load torque)	Nm	110	90	50
最大加速力矩 (Max. acceleration torque)	Nm	198	162	90
急停扭矩 (Emergency stop torque)	Nm	330	270	150

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	900N	空载力矩 20℃ (No-load torque)	$\leq 0.2\text{Nm}$
容许最大轴向载荷 (Max. axial load)	1200N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000\text{h}$
噪音 (Noise)	$\leq 65\text{db}$	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	18arcmin	WPL系列	Tel/电话: 0533-6288333 6288444
		P2 L3	Fax/传真: 0533-6288411
			Web/网址: www.newstart.cn

未注线性尺寸极限偏差  
Unmarked tolerance

0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机  
Precision Planetary  
Gear Boxes



WPL080L3-i-P2-S2  
19-40-70-90-M5

A. WPL. 080.