


减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩(Rated load torque)		Nm 1780	1153	800	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm 3204	2075.4	1440	120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm 5340	3459	2400	400-1000	±2
精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)		18000N	空载力矩20℃(No-load torque) ≤ 1.5Nm		 紐氏達特	
容许最大轴向载荷 (Max.axial load)		28000N	润滑(Lubrication) 合成润滑脂 (Synthetic grease)			
额定输入转速 (Nominal input speed)		1500r/min	使用环境温度(Operation temperature) -15℃~+90℃		PS190L3-i-P2-S2 35-79-114.3-200-M12	
最大输入转速 (Max input speed)		3000r/min	使用寿命(Service life) ≥20000h			
噪音 (Noise) ≤ 72db		防护等级(Protection grade) IP54				
回程间隙 (Backlash)		12arcmin	PS 系列		A. PS. 190.	
		P2 L3				
				Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		