


减速比 (Ratio i)		3	4	5	6	8	10	3-6	±0.3
额定承载扭矩(Rated load torque)	Nm	22	45	41	26	18	15	6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	39.6	81	73.8	46.8	32.4	27	30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	66	135	123	78	54	45	120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	480N	空载力矩20℃(No-load torque)				≤ 0.1Nm		 纽氏達特	PS070L1-i-P2-S2 14-30-50-70-M5
容许最大轴向载荷 (Max.axial load)	600N	润滑(Lubrication)				合成润滑脂 (Synthetic grease)			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)				-15℃~+90℃			
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)				≥20000h			
噪音 (Noise)	≤ 60db	防护等级(Protection grade)				IP54			
回程间隙 (Backlash)	8arcmin				PS系列	Tel/电话: 0533-6288333 6288444		A. PS.	070.
					P2 L1	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			