



减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩(Rated load torque)		Nm110	90	50	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm198	162	90	120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm330	270	150	400-1000	±2
精密行星减速机技术参数					精密行星减速机	
					Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)		900N	空载力矩20℃(No-load torque)		≤ 0.2Nm	
容许最大轴向载荷 (Max.axial load)		1200N	润滑(Lubrication)		合成润滑脂 (Synthetic grease)	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度(Operation temperature)		-15℃~+90℃	
最大输入转速 (Max input speed)		6000r/min	使用寿命(Service life)		≥20000h	
噪音 (Noise)		≤ 60db	防护等级(Protection grade)		IP54	
回程间隙 (Backlash)		12arcmin	PS系列		Tel/电话: 0533-6288333 6288444	
			P2 L3		Fax/传真: 0533-6288411	
					Web/网址: www.newstart.cn	
					PS090L3-i-P2-S2 19-40-70-90-M5	
					A. PS. 090.	