


| | | | | | | |
|-----------------------------------|-----------|--------------------------------|------------------------------|-----|---|------|
| 减速比 (Ratio i) | | 60/64/80/160/256 | 100/120/200/320 | 512 | 6-30 | ±0.5 |
| 额定承载扭矩 (Rated load torque) | Nm | 110 | 90 | 50 | 30-120 | ±0.8 |
| 最大加速力矩 (Max. acceleration torque) | Nm | 198 | 162 | 90 | 120-400 | ±1.2 |
| 急停扭矩 (Emergency stop torque) | Nm | 330 | 270 | 150 | 400-1000 | ±2 |
| 精密行星减速机技术参数 | | | | | 精密行星减速机 | |
| 容许最大径向载荷 (Max. radial load) | 900N | 空载力矩20℃ (No-load torque) | ≤ 0.2Nm | | Precision Planetary Gear Boxes | |
| 容许最大轴向载荷 (Max. axial load) | 1200N | 润滑 (Lubrication) | 合成润滑油 (Synthetic grease) | |  | |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | -15℃~+90℃ | | PS090L3-i-P2-S2 | |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命 (Service life) | ≥20000h | | 14-30-50-70-M4 | |
| 噪音 (Noise) | ≤ 60db | 防护等级 (Protection grade) | IP54 | | A. PS. 090. | |
| 回程间隙 (Backlash) | 12arcmin | PS系列 | Tel/电话: 0533-6288333 6288444 | | | |
| | | P2 L3 | Fax/传真: 0533-6288411 | | | |
| | | | Web/网址: www.newstart.cn | | | |