


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5
额定承载扭矩(Rated load torque)		Nm		360							30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm		540							120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm		1080							400-1000	±2
精密行星减速机技术参数											精密行星减速机	
容许最大径向载荷 (Max.radial load)		2700N		空载力矩20℃(No-load torque)				≤ 0.36Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		1350N		润滑(Lubrication)				合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)		2000r/min		使用环境温度(Operation temperature)				-15℃~+90℃			紐氏達特	
最大输入转速 (Max input speed)		4000r/min		使用寿命(Service life)				≥20000h			PW140L2-i-S2-19-55-95-115-M8	
噪音 (Noise)		≤ 70db		防护等级(Protection grade)				IP54			A. PW. 140.	
回程间隙 (Backlash)		10arcmin				PW系列		Tel/电话: 0533-6288333 6288444				
						P2 L2		Fax/传真: 0533-6288411				
								Web/网址: www.newstart.cn				

未注线性尺寸极限偏差
Unmarked tolerance

0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2