



减速比 (Ratio i)		1	2					3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	360	330					6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	540	495					30-120	±0.8
急停扭矩 (Emergency stop torque)	Nm	1080	990					120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机	
								Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	2700N	空载力矩20℃ (No-load torque)			≤ 0.36Nm				
容许最大轴向载荷 (Max. axial load)	1350N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃				
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)			≥20000h				
噪音 (Noise)	≤ 70db	防护等级 (Protection grade)			IP54			PW140L1-i-S2-22-58-110-145-M8	
回程间隙 (Backlash)	6arcmin	PW系列			Tel/电话: 0533-6288333 6288444			A. PW. 140.	
		P2 L1			Fax/传真: 0533-6288411				
					Web/网址: www.newstart.cn				

未注线性尺寸极限偏差
Unmarked tolerance

0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机
Precision Planetary
Gear Boxes



NEWSTART®
紐氏達特

PW140L1-i-S2-22-58-
110-145-M8

A. PW.	140.
--------	------