


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩 (Rated load torque)		Nm									360	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm									540	120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm									1080	400-1000	±2
精密行星减速机技术参数											精密行星减速机		
容许最大径向载荷 (Max.radial load)		2700N	空载力矩20℃ (No-load torque)				≤ 0.36Nm				Precision Planetary Gear Boxes		
容许最大轴向载荷 (Max.axial load)		1350N	润滑 (Lubrication)				合成润滑脂 (Synthetic grease)						
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)				-15℃ +90℃				NEWSTART 纽氏達特		
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)				≥20000h				PW140L2-i-S2-0P1		
噪音 (Noise)		≤ 70db	防护等级 (Protection grade)				IP54						
回程间隙 (Backlash)		10arcmin				PW系列		Tel/电话: 0533-6288333 6288444				A. PW. 140.	
						P2 L2		Fax/传真: 0533-6288411					
								Web/网址: www.newstart.cn					