


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩 (Rated load torque)		Nm		360							30-120	±0.8	
最大加速力矩 (Max. acceleration torque)		Nm		540							120-400	±1.2	
急停扭矩 (Emergency stop torque)		Nm		1080							400-1000	±2	
精密行星减速机技术参数											精密行星减速机		
容许最大径向载荷 (Max. radial load)		2700N		空载力矩20℃ (No-load torque)				≤ 0.36Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)		1350N		润滑 (Lubrication)				合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)		2000r/min		使用环境温度 (Operation temperature)				-15℃ +90℃				纽氏达特	
最大输入转速 (Max input speed)		4000r/min		使用寿命 (Service life)				≥20000h				PW140L2-i-K2-24-58-110-145-M8	
噪音 (Noise)		≤ 70db		防护等级 (Protection grade)				IP54					
回程间隙 (Backlash)		10arcmin				PW系列		Tel/电话: 0533-6288333 6288444				A. PW. 140.	
						P2 L2		Fax/传真: 0533-6288411					
								Web/网址: www.newstart.cn					