


| | | | | | | | | | | |
|-----------------------------------|-----------|--------------------------------|------|-------|------|---|-----|--|--|------|
| 减速比 (Ratio i) | | 3 | 4 | 5 | 6 | 8 | 10 | | 3-6 | ±0.3 |
| 额定承载扭矩 (Rated load torque) | Nm | 360 | 360 | 360 | 360 | 360 | 330 | | 6-30 | ±0.5 |
| 最大加速力矩 (Max. acceleration torque) | Nm | 540 | 540 | 540 | 540 | 540 | 495 | | 30-120 | ±0.8 |
| 急停扭矩 (Emergency stop torque) | Nm | 1080 | 1080 | 1080 | 1080 | 1080 | 990 | | 120-400 | ±1.2 |
| | | | | | | | | | 400-1000 | ±2 |
| 精密行星减速机技术参数 | | | | | | | | | 精密行星减速机 | |
| 容许最大径向载荷 (Max. radial load) | 2700N | 空载力矩20℃ (No-load torque) | | | | ≤ 0.36Nm | | | Precision Planetary Gear Boxes | |
| 容许最大轴向载荷 (Max. axial load) | 1350N | 润滑 (Lubrication) | | | | 合成润滑油 (Synthetic grease) | | |  纽氏达特 | |
| 额定输入转速 (Nominal input speed) | 2000r/min | 使用环境温度 (Operation temperature) | | | | -15℃~+90℃ | | | | |
| 最大输入转速 (Max input speed) | 4000r/min | 使用寿命 (Service life) | | | | ≥20000h | | | PW140L1-i-K2-OP1 | |
| 噪音 (Noise) | ≤ 70db | 防护等级 (Protection grade) | | | | IP54 | | | | |
| 回程间隙 (Backlash) | 8arcmin | | | PW系列 | | Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn | | | A. PW. 140. | |
| | | | | P2 L1 | | | | | | |