



减速比 (Ratio i)		3	4	5	6	8	10
额定承载扭矩 (Rated load torque)	Nm	585	585	585	585	585	544
最大加速力矩 (Max. acceleration torque)	Nm	878	878	878	878	878	816
急停扭矩 (Emergency stop torque)	Nm	1755	1755	1755	1755	1755	1632
精密行星减速机技术参数							
容许最大径向载荷 (Max. radial load)	3800N	空载力矩20℃ (No-load torque)				≤ 0.72Nm	
容许最大轴向载荷 (Max. axial load)	1900N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)	
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)				-15℃~+90℃	
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)				≥20000h	
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)				IP54	
回程间隙 (Backlash)	8arcmin	PW系列				Tel/电话: 0533-6288333 6288444	
		P2 L1				Fax/传真: 0533-6288411	
						Web/网址: www.newstart.cn	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机 Precision Planetary Gear Boxes	
 紐氏達特	
PW170L1-i-S2-38-80- 180-215-M12	
A. PW.	170.

