

1

2

3

4

5




6

A

B

C

D



A

B


C

D

减速比 (Ratio i)	12	15	16	20	25	30	32	40	50
额定承载扭矩 (Rated load torque) Nm	585								
最大加速力矩 (Max. acceleration torque) Nm	878								
急停扭矩 (Emergency stop torque) Nm	1755								

精密行星减速机技术参数			
容许最大径向载荷 (Max. radial load)	3800N	空载力矩20℃ (No-load torque)	$\leq 0.72Nm$
容许最大轴向载荷 (Max. axial load)	1900N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)	$\geq 20000h$
噪音 (Noise)	$\leq 72db$	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	10arcmin	PW系列	Tel/电话: 0533-6288333 6288444
		P2 L2	Fax/传真: 0533-6288411
			Web/网址: www.newstart.cn

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机 Precision Planetary Gear Boxes	
	
PW170L2-i-S2-24-55-110-145-M8	
A. PW.	170.

1

2

3

4

5

6