


减速比 (Ratio i)		1	2							3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	585	544							6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	878	816							30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	1755	1632							120-400	±1.2
										400-1000	±2
精密行星减速机技术参数										精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	3800N	空载力矩20℃ (No-load torque)					≤ 0.72Nm			 纽氏达特	
容许最大轴向载荷 (Max.axial load)	1900N	润滑 (Lubrication)					合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)					-15℃~+90℃			PW170L1-i-K2-0P1	
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)					≥20000h				
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)					IP54				
回程间隙 (Backlash)	6arcmin				PW系列		Tel/电话: 0533-6288333 6288444			A. PW. 170.	
					P2 L1		Fax/传真: 0533-6288411				
							Web/网址: www.newstart.cn				