


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩(Rated load torque)	Nm	585									30-120	±0.8	
最大加速力矩 (Max.acceleration torque)	Nm	878									120-400	±1.2	
急停扭矩 (Emergency stop torque)	Nm	1755									400-1000	±2	
精密行星减速机技术参数											精密行星减速机		
容许最大径向载荷 (Max.radial load)	3800N	空载力矩20℃(No-load torque)				≤ 0.72Nm					Precision Planetary Gear Boxes		
容许最大轴向载荷 (Max.axial load)	1900N	润滑(Lubrication)				合成润滑脂 (Synthetic grease)							
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度(Operation temperature)				-15℃~+90℃							
最大输入转速 (Max input speed)	3000r/min	使用寿命(Service life)				≥20000h					PW170L2-i-K2-0P1		
噪音 (Noise)	≤ 72db	防护等级(Protection grade)				IP54							
回程间隙 (Backlash)	10arcm				PW系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					A. PW. 170.	
					P2 L2								

未注线性尺寸极限偏差 Unmarked tolerance	
----------------------------------	--

0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	+2

精密行星减速机
Precision Planetary
Gear Boxes



PW170L2-i-K2-OP1

A. PW.	170.
--------	------