



减速比 (Ratio i)		60	64	80	100	120	125	150	160	200
额定承载扭矩 (Rated load torque)	Nm					585				
最大加速力矩 (Max. acceleration torque)	Nm					878				
急停扭矩 (Emergency stop torque)	Nm	1755								
精密行星减速机技术参数										
容许最大径向载荷 (Max. radial load)	3800N	空载力矩20℃ (No-load torque)				≤ 0.72Nm				
容许最大轴向载荷 (Max. axial load)	1900N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)				-15℃~+90℃				
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)				≥20000h				
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)				IP54				
回程间隙 (Backlash)	12arcmin				PW系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				
					P2 L3					

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2
精密行星减速机 Precision Planetary Gear Boxes	
	
PW170L3-i-K2-22-58- 110-145-M8	
A. PW.	170.