


减速比 (Ratio i)		1	2						3-6	±0.3
额定承载扭矩 (Rated load torque)		Nm	585	544					6-30	±0.5
最大加速力矩 (Max. acceleration torque)		Nm	878	816					30-120	±0.8
急停扭矩 (Emergency stop torque)		Nm	1755	1632					120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
									Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	3800N	空载力矩20℃ (No-load torque)				≤ 0.72Nm				
容许最大轴向载荷 (Max. axial load)	1900N	润滑 (Lubrication)				合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)				-15℃~+90℃			PW170L1-i-K2-38-80-180-215-M12	
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)				≥20000h				
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)				IP54			A. PW. 170.	
回程间隙 (Backlash)	6arcmin					PW系列				
						P2 L1				
						Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				

未注线性尺寸极限偏差
Unmarked tolerance

0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2