


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5
额定承载扭矩(Rated load torque) Nm		585									30-120	±0.8
最大加速力矩 (Max.acceleration torque) Nm		878									120-400	±1.2
急停扭矩 (Emergency stop toque) Nm		1755									400-1000	±2
精密行星减速机技术参数											精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)		3800N	空载力矩20℃(No-load torque)				≤ 0.72Nm				 紐氏達特	
容许最大轴向载荷 (Max.axial load)		1900N	润滑(Lubrication)				合成润滑油 (Synthetic grease)					
额定输入转速 (Nominal input speed)		1500r/min	使用环境温度(Operation temperature)				-15℃~+90℃				PW170L2-i-K2-22-58- 110-145-M8	
最大输入转速 (Max input speed)		3000r/min	使用寿命(Service life)				≥20000h					
噪音 (Noise)		≤ 72db	防护等级(Protection grade)				IP54				A. PW. 170.	
回程间隙 (Backlash)		10arcmin			PW系列 P2 L2		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					

未注线性尺寸极限偏差
Unmarked tolerance

0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2