


减速比 (Ratio i)		1	2						3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	25	24						6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	38	36						30-120	±0.8
									120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	75	72						400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max. radial load)									Precision Planetary	
容许最大轴向载荷 (Max. axial load)	700N	空载力矩20℃ (No-load torque)			≤ 0.1Nm				Gear Boxes	
容许最大轴向载荷 (Max. axial load)	350N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃				纽氏达特	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h				PW065L1-i-S2-14-30	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)			IP54				50-70-M4	
回程间隙 (Backlash)	6arcmin	PW系列			Tel/电话: 0533-6288333 6288444				A. PW. 065.	
		P2 L1			Fax/传真: 0533-6288411					
					Web/网址: www.newstart.cn					