


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩 (Rated load torque)	Nm	25									30-120	±0.8	
最大加速力矩 (Max.acceleration torque)	Nm	38									120-400	±1.2	
急停扭矩 (Emergency stop torque)	Nm	75									400-1000	±2	
精密行星减速机技术参数											精密行星减速机 Precision Planetary Gear Boxes		
容许最大径向载荷 (Max.radial load)	700N	空载力矩 0N (No-load torque)				≤ 0.1Nm							
容许最大轴向载荷 (Max.axial load)	350N	润滑 (lubrication)				合成润滑油 (Synthetic grease)							
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)				-15℃~+90℃							
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h							
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)				IP54					PW65L1-i-S2-14-30-50-70-M5		
回程间隙 (Backlash)	8arcmin				PW系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				A. PW. 065.		
					P2 L1								