


减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩(Rated load torque)		Nm	25	25	25	25	24		6-30	±0.5
最大加速力矩 (Max.acceleration torque)		Nm	38	38	38	38	36		30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	75	75	75	75	72		120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max.radial load)		700N	空载力矩20℃ (No-load torque)			≤ 0.1Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		350N	润滑 (lubrication)			合成润滑脂 (Synthetic grease)			 紐氏達特	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃			PW65Li-i-S2-14-30- 50-70-M4	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)			≥20000h				
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)			IP54			A. PW. 065.	
回程间隙 (Backlash)		8arcmin			PW系列		Tel/电话: 0533-6288333 6288444			
					P2 L1		Fax/传真: 0533-6288411			
							Web/网址: www.newstart.cn			