


减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	45	45	45	45	45	42		6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	68	68	68	68	68	63		30-120	±0.8
急停扭矩 (Emergency stop torque)	Nm	135	135	135	135	135	126		120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	950N	空载力矩 0N (No-load torque)				≤ 0.1Nm			 纽氏达特	
容许最大轴向载荷 (Max. axial load)	425N	润滑 (lubrication)				合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)				-15℃~+90℃			PW75L1-i-S2-8-30- 38.1-147.14-M4	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h				
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)				IP54				
回程间隙 (Backlash)	8arcmin				FW 系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		A. PW.	075.
					P2 L1					