


减速比 (Ratio i)		1	2						3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	25	24						6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	45	43.2						30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	75	72						120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	950N	空载力矩20℃ (No-load torque)				≤ 0.1Nm				
容许最大轴向载荷 (Max.axial load)	425N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃				
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h				
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)				IP54			PW75L1-i-S2-8-25-	38.1-□47.14-M4
回程间隙 (Backlash)	6arcmin			PW系列	Tel/电话: 0533-6288333 6288444				A. PW.	075.
				P2 L1	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					