



减速比 (Ratio i)	1	2						
额定承载扭矩 (Rated load torque) Nm	45	42						
最大加速力矩 (Max. acceleration torque) Nm	68	63						
急停扭矩 (Emergency stop torque) Nm	135	126						
精密行星减速机技术参数								
容许最大径向载荷 (Max. radial load)	950N	空载力矩20℃ (No-load torque)		$\leq 0.1Nm$				
容许最大轴向载荷 (Max. axial load)	425N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		$-15^{\circ}C \sim +90^{\circ}C$				
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		$\geq 20000h$				
噪音 (Noise)	$\leq 63db$	防护等级 (Protection grade)		IP54				
回程间隙 (Backlash)	6arcmin			PW系列		Tel/电话: 0533-6288333 6288444		
				P2 L1		Fax/传真: 0533-6288411		
						Web/网址: www.newstart.cn		

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2
精密行星减速机 Precision Planetary Gear Boxes	
 纽氏達特	
PW75L1-i-K2-14-30-50-70-M5	
A. PW.	075.