


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩(Rated load torque)		Nm		45							30-120	±0.8	
最大加速力矩 (Max.acceleration torque)		Nm		68							120-400	±1.2	
急停扭矩 (Emergency stop toque)		Nm		135							400-1000	±2	
精密行星减速机技术参数											精密行星减速机		
容许最大径向载荷 (Max.radial load)		950N	空载力矩20℃ (No-load torque)				≤ 0.1Nm				Precision Planetary Gear Boxes		
容许最大轴向载荷 (Max.axial load)		425N	润滑 (Lubrication)				合成润滑脂 (Synthetic grease)						
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃				纽氏达特		
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)				≥20000h				PW75L1-i-S2-14-30-50-70-M4		
噪音 (Noise)		≤ 63db	防护等级 (Protection grade)				IP54						
回程间隙 (Backlash)		10arcmin				PW系列		Tel/电话: 0533-6288333 6288444					
						P2 L2		Fax/传真: 0533-6288411				A. PW. 075.	
								Web/网址: www.newstart.cn					