


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	45									30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	68									120-400	±1.2
急停扭矩 (Emergency stop toque)	Nm	135									400-1000	±2
精密行星减速机技术参数											精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	950N	空载力矩20℃(No-load torque)				≤ 0.1Nm					 NEWSTART® 纽氏速特	
容许最大轴向载荷 (Max.axial load)	425N	润滑(Lubrication)				合成润滑脂 (Synthetic grease)						
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)				-15℃~+90℃						
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)				≥20000h						
噪音 (Noise)	≤ 63db	防护等级(Protection grade)				IP54						
回程间隙 (Backlash)	10arcmin				PW系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				PW75L1-i-S2-14-30-50-70-M4	
					P2 L2						A. PW.	075.